## **EAST Search History**

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	0	"An enclosure for an electronic system comprising: a first chassis operable to enclose a plurality of electronic components, the first chassis comprising a first face and a second face opposite the first face; a second chassis operable to enclose one or more power supplies, comprising a third face; and one or more cords running from the first fact to the third face, the one or more cords operable to supply power from the one or more power supplies to at least one of the plurality of electronic components; and wherein the third face and the first face define an indentation, and the second chassis is indented from the first chassis".clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:37
L2	19550	enclosure and (electronic adj system) and (first adj chassis) and (electronic adj component) and (first adj face) and (second adj face) and (second adj chassis) and (power adj supply) and (third face) and cord indentation.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:41
L3	0	enclosure and (electronic adj system) and (first adj chassis) and (electronic adj component) and (first adj face) and (second adj face) and (second adj chassis) and (power adj supply) and (third face) and cord and indentation.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:41
L4	0	"An enclosure for an electronic system comprising: a first chassis, operable to enclose a plurality of electronic components, comprising: a first face; a second face opposite the first face; a third face, wherein the plane of the third face is perpendicular to the planes of the first face and the second face; a second, chassis operable to enclose one or more power supplies, the second chassis having a fourth face indented from the first face; and one or more cords running from the first fact to the fourth face, the one or more cords operable to supply power from the one or more power supplies to at least one of the plurality of electronic components".clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/07/19 15:42
L5	0	enclosure and (electronic adj system) and (first adj chassis) and (electronic adj component) and (first adj face) and (second adj face) and (third adj face) and perpendicular and (second adj chassis) and (power adj supply) and (fourth adj face) and indent\$4 and cord.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:46
L6		"An enclosure for an electronic system comprising: means for enclosing a plurality of electronic components, defined by a first face and a second face opposite the first face; means for making electrical connections disposed through the first face; means for enclosing one or more power supplies, defined at least in part by a third face; and wherein the third face and the first face define an indentation".clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:48
L7	0	enclosure and (electronic adj system) and "means for enclosing" and (electronic adj component) and (first adj face) and (second adj face) and "means for making electrical connections" and (power adj supply) and (third adj face) and indentation.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 15:51
S1	18	(("6583989") or ("4967155") or ("5216579") or ("6392901") or ("5450285") or ("5515239") or ("6742068") or ("4744005") or ("6754068")).PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	OFF.	2007/05/29 13:34
S2	9	(("6583989") or ("4967155") or ("5216579") or ("6392901") or ("5450285") or ("5515239") or ("6742068") or ("4744005") or ("6754068")).PN.	USPAT	OR	OFF	2007/05/24 16:22

## **EAST Search History**

				·		
\$3	2444	(361/724-727).CCLS.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/07/19 12:50
S4	1208	(312/223.1,233.2,223.6).CCLS.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/07/19 12:52
S5	3414	S3 or S4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 12:52
S6	2786	S5 not keyboard	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 12:52
S7	2537	S6 not portable	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 13:15
\$8	599	S7 and power and (cord or cable)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 13:16
S9	20	("20020181202" "4744005" "4967155" "5216579" "5450285" "5515 239" "6392901" "6583989" "6742068" "6754068").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 14:44
S10	0	"An electronic device comprising: a first housing comprising a first face; a second housing comprising a second face; the second face indented from the first face; a plurality of electronic components housed in the first housing; one or more power supplies housed in the second housing; and the electronic components operable to be powered by a cord to the one or more of the plurality of power supplies, the cord running from the indented second face to the first face".clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/19 14:51
S11	0	(electronic adj device) and (first adj housing) and (first adj face) and (second adj housing) and (second adj face) and indented and (electronic adj components) and (power adj supplies) and cord. clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/07/19 14:57